HTW

HOME RANGE

3 YEARS WARRANTY TOTAL QUALITY COMMITMENT

5 YEARS WARRANTY COMPRESSOR QUALITY COMMITMENT

21dB DEPENDING ON MODEL

A++ SEER

A+ SCOP

A+++ SCOP Warmer





Data sheet

SPLIT 1X1

PURE LIGHT UV

UV

GOLDEN FIN Protection

Mode silent

Turbo button

Function I feel

Timer

Filter anti-bacteria

			HTWS026PLUV	HTWS035PLUV	HTWS052PLUV	HTWS071PLUV
		IU	HTWS026PLUV-I	HTWS035PLUV-I	HTWS052PLUV-I	HTWS071PLUV-I
MODELS		OU	HTWS026PLUV-O	HTWS035PLUV-O	HTWS052PLUV-O	HTWS071PLUV-O
Electrical power supply		V,F,HZ	220–240V (1 Fase ~ 50Hz)			
Connection			Outdoor unit			
PERFORMANCE						
Capacity refrigeration	Capacity	kW	2.500 (660 - 2.930)	3.500 (660 - 3.800)	5.200 (1.610 - 5.420)	7.100 (1.110 - 7.800)
		Btu/h	8.500 (2.250 - 10.000)	11.940 (2250 - 12.900)	17.700 (5.500 - 18.500)	24.200 (3.800 - 26.600)
	Consumption	W	650 (250 - 1.450)	1.150 (250 - 1.800)	1.690 (350 - 2.400)	2.100 (450 - 3.350)
	SEER	–	6,1	6,1	6,1	6,1
	Energy classification	Cold	A++	A++	A++	A++
Capacity heating	Capacity	kW	2.600 (660 - 3.070)	3.500 (660 - 3.950)	5.200 (1.610 - 5.560)	7.100 (1370 - 8.200)
		Btu/h	8.800 (2.250 - 10.500)	11.940 (2.250 - 12.900)	17.700 (5.500 - 18.500)	24.200 (3.800 - 26.600)
	Consumption	W	630 (250 - 1600)	980 (250 - 1.800)	1.460 (350 - 2.400)	1.960 (450 - 3.350)
	SCOP	–	4	4	4	4
	Energy classification	Hot	A+	A+	A+	A+
CHARACTERISTICS						
interior unit	Sound power	dB(A)	50/47/44	52/49/46	56/51/48	59/54/51
	Sound pressure (H/M/L)	dB(A)	40/37/34/21	42/39/36/23	44/41/38/24	46/43/40/24
	Airflow	m³/h	≥500	≥550	≥850	≥1200
	Operating temperature	°C	16 - 32	16 - 32	16 - 32	16 - 32
Exterior unit	Sound power	dB(A)	62	64	65	69
	Sound pressure	dB(A)	52	52	54	57
	Airflow	m³/h	2180	2180	2300	3350
	Operating temperature	°C	-15~52	-15~52	-15~52	-15~52
	Compressor		GMCC	GMCC	GMCC	Highly
Refrigerant	Type / Load	R32/Kg	0,57	0,6	1,07	1,51
	Additional load> 5	g/m	15	15	15	15
DIMENSIONS AND WEIGHT						
interior unit	Net dimensions (W×H×D)	mm	790×200×270	790×200×270	900×220×291	1025x320x235
	Gross dimensions (W×H×D)	mm	870×265×335	870×265×335	970×290×345	1105x315x405
	Net/gross weight	Kg	8/9	8.5/10	10.5/12.5	14/16
Exterior unit	Net dimensions (W×H×D)	mm	780×542×271	780×542×271	782×580×287	860x720x320
	Gross dimensions (W×H×D)	mm	900×600×340	900×600×340	905×640×365	1015x775x445
	Net/gross weight	Kg	29/32	30/33	31/35	44/49
CONNECTIONS						
Pipeline refrigerator	Liquid - Gas	In.	1/4" - 3/8"	1/4" - 3/8"	1/4" - 1/2"	3/8" - 5/8"
	Max length	m	20	20	25	25
	Max unevenness	m	15	15	15	15
Electric connections	Feeding	mm	2 x 2,5 + T	2 x 2,5 + T	2 x 2,5 + T	2 x 2,5 + T
	Interconnection	mm	4 x 2,5	4 x 2,5	4 x 2,5	4 x 2,5
EAN CODE			8435483828384	8435483828377	8435483828360	8435483828353

Notes:
Capacity data under standard conditions. Actual data will vary depending on where the equipment is installed and how it is used.
The dimensions of the electrical wiring are approximate, it should be calculated based on the conditions of the installation itself

GIATSU reserves all rights to modify models and technical data without prior notice. Valid information except typographical or printing error.