Sanitary hot water combo
serie **VAX300**

HTW
HIGH TECHNOLOGY WORLD

3 YEAR GUARANTEE TOTAL QUALITY COMMITMENT

COP 2,8

A ACS



MODEL			HTW-ATS-0-300VAX	
Power supply		V,F,HZ	220-240V (1 Phase ~ 50Hz)	
Heat source		–	Mode ECO	Mode E-HEATER
POWER				
Heating capacity	Capacity	kW	2,02	1,6
	Current	A	3,2	6,8
	COP	–	2,89	1
	Consumption	W	700	1.600
PERFORMANCE				
Tank capacity		–	300	
Tank material			Stainless steel SUS 304	
Water production*		L/h	45	
Operating temperature		°C	-5°C ~ 43°C	
Water temperature		°C	Default 60°C	
Sound pressure		dB(A)	40	
Refrigerant	Type	–	R134A	
	Charged	Kg	0,8	
DIMENSIONS AND WEIGHT				
Net dimensions (Ø x Al)		mm	Ø640×1.845	
Gross dimensions (AnxAlxPr)		mm	695×1.975×695	
Net/gross weight		Kg	110/120	
CONNECTIONS				
Hydraulic connections	Water inlet	in	G 3/4	
	Water outlet	in	G 3/4	
	Drain	in	G 3/4	
	Valve set	in	G 3/4	
Solar heat exchanger	Water inlet	in	G 3/4	
	Water outlet	in	G 3/4	
	Material	–	Aluminium alloy SUS316	
EAN CODE			**8435483802858**	

NOTES:
1. During the disinfection action, the maximum temperature can reach 70°C through the electric heating.
2. *With a ΔT of 40°C.

R134A — Refrigerant gas
Easy — Easy installation
Intelligent defrosting
Anti-legionella function
Solar energy compatibility
Stainless steel tank
Heater + Water-Heater — Replace heater and water-heater
°C 70 — Maximum water outlet temperature

40dB DEPENDING MODEL

HTW reserves all rights to modificate models and technical information without prior notice.
Valid information except typographical or printing error.

HTW