HIGH TECHNOLOGY WORLD

RANGE **OFFICE**

3 YEARS GUARANTEE TOTAL QUALITY COMMITMENT

5 YEARS GUARANTEE COMPRESSOR QUALITY COMMITMENT

A++ SEER

A+ SCOP



Technical data

CASSETTE

CIRCLE R32

R-32

DC inverter — DC Inverter compressor and fans

Night mode

Turbo button

Defrost function

Remote control

Child lock

Auto-diagnosis

24h timer

Anti corrossion protection

MODELS			HTW-C6-035CIRR32	HTW-C9-052CIRR32	HTW-C9-071CIRR32	HTW-C9-105CIRR32
		INT.	HTW-C6I-035CIRR32	HTW-C9I-052CIRR32	HTW-C9I-071CIRR32	HTW-C9I-105CIRR32
		EXT.	HTW-U0-035SKR32	HTW-U0-052SKR32	HTW-U0-071SKR32	HTW-U0-105SKR32
Power supply		V,F,HZ	220-240V (1 Phase ~ 50Hz)			
PERFORMANCE						
Cooling	Performance	kW	3,5	5,2	7	10,5
		Btu/h	11.942	17.743	23.885	36.000
	Consommation	W	1.250	1.250	2.230	3.280
	SEER	-	6,1	6,1	6,1	6,1
	Energy class	Cold	A++	A++	A++	A++
Heating	Performance	kW	3,5	5,5	7	10,5
		Btu/h	11.942	18.767	23.885	36.000
	Consommation	W	1.000	1.600	1.840	2.630
	SCOP	-	4	4	4	4
	Energy class	Heat	A+	A+	A+	A+
FEATURES						
Indoor unit	Sound power H/M/L	dB(A)	57/54/49	55/52/49	55/52/49	63/59/54
	Sound pressure H/M/L	dB(A)	47/44/39	42/39/36	42/39/36	53/49/44
	Air flow	m^3/h	700	1.250	1.250	2.000
	Operation temperature	°C	16~31	16~31	16~31	16~31
Outdoor unit	Sound power	dB(A)	62	66	68	69
	Sound pressure	dB(A)	53	58	60	59
	Air flow	m^3/h	1.800	2.800	3.300	5.500
	Ambient temperature operation	°C	-15~48	-15~48	-15~48	-15~48
	Compressor		CRSS	CRSS	CRSS	GMCC
Refrigerant	Type/Charge	R32/Kg	0,9	1,05	1,5	3,2
	Additional charge > 5	g/m	16	16	16	30
DIMENSIONS AND WEIGHT						
Indoor unit	Net dimensions (L×H×D)	mm	570×260×570 650×28×650 (panel)	840×225×840 950×65×950 (panel)	840×225×840 950×65×950 (panel)	840×300×840 950×65×950
	Net weight/panel	Kg	19/2,2	27,5/8	27,5/8	33/8
Outdoor unit	Net dimensions (L×H×D)	mm	830×540×325	890×598×372	960×700×396	1.020x998x396
	Net weight	Kg	30	40	45	75
CONNECTIONS						
Cooling pipe	Liquid-Gas	inch	1/4" - 3/8"	1/4"-1/2"	1/4"-5/8"	3/8"-5/8"
	Length max.	m	20	30	30	30
	Slope max.	m	15	15	15	15
Electrical connections	Supply	mm	2 × 2,5+T	2 × 2,5+T	2 × 2,5+T	2 × 2,5+T
	Connection	mm	3 × 2,5+T	3 × 2,5+T	3 × 2,5+T	3 × 2,5+T
EAN CODE	Ensemble		8435483818422	8435483817463	8435483817432	8435483824140

HTW reserves the right to change models and technical data without prior notice. Valid information except typo or printing.