HIGH TECHNOLOGY WORLD

RANGE **HOME**

3 YEARS WARRANTY TOTAL QUALITY COMMITMENT

5 YEARS WARRANTY COMPRESSOR QUALITY COMMITMENT

A+++ SEER

A++ SCOP

A+++ SCOP *warmer

Technical data





SPLIT MURAL
INNOVA

R-32

DC inverter

DC Inverter compressor and fans

Night mode

Auto-diagnosis

Auto restart function

Remote control

Drain by both sides

Anti-cold function

Defrost function

MODEL

			HTWS026INNR32	HTWS035INNR32
		IN.	HTWS026INNR32-INT	HTWS035INNR32-INT
		OUT.	HTWS026INNR32-EXT	HTWS035INNR32-EXT
Power Supply		V,P,HZ	220-240V (1 Phase ~ 50Hz)	
PERFORMANCE				
Cooling	Capacity (min.-max.)	W	2.600 (400-3.300)	3.500 (550-4.000)
		Btu/h	8.871 (1.365-11.260)	11.942 (1.877-13.648)
	Consumption (min.-max.)	W	650 (150-1.430)	875 (180-1.560)
	SEER	-	8,6	8,6
	Energy class	Cold	A+++	A+++
Heating	Capacity (min.-max.)	kW	2.800 (400-4.100)	3.800 (600-5.130)
		Btu/h	9.554 (1.365-13.989)	12.966 (2.047-17.504)
	Consumption (min.-max.)	W	710 (180-1.550)	975 (220-1.800)
	SCOP	-	4,6	4,6
	Energy class	Heat	A++	A++
FEATURES				
Indoor unit	Sound power	dB(A)	51/47/34/32	53/48/35/33
	Sound pressure	dB(A)	38/34/21/18	40/35/22/20
	Air flow	m^3/h	520/440/230/150	580/500/300/230
	Selectable temperature	°C	16~31	16~31
Outdoor unit	Sound power	dB(A)	52	53
	Sound pressure	dB(A)	61	62
	Air flow	m^3/h	1.800	2.800
	Operating temperature cold	°C	-18~52 | -20~24	-18~52 | -20~24
	Compressor		Panasonic	Mitsubishi
Refrigerant	Type/Charge	R32/Kg	0,7	0,9
	Additional charge>5	g/m	12	12
Design pressure		Mpa	4,3/2,5	4,3/2,5
Climatised perimeter (depending on room conditions)		m^2	18	24
DIMENSIONS AND WEIGHT				
Indoor unit	Net dimensions (WxHxD)	mm	910x303x200	910x303x200
	Net weight	Kg	12	12
Outdoor unit	Net dimensions (WxHxD)	mm	830x540x325	890x598x372
	Net weight	Kg	30	38
CONNECTIONS				
Refrigeration pipe	Liquid-Gas	inch	1/4"-3/8"	1/4"-3/8"
	Max. length	m	20	20
	Max. slope	m	10	10
Electrical connections	Supply	mm	2x2,5+T	2x2,5+T
	Connection	mm	3x2,5+T	3x2,5+T
EAN CODE	Set		8435483813809	8435483813793

HTW reserves all rights to modify models and technical data without prior notice. Valid information except typographical or printing error.