HIGH TECHNOLOGY WORLD

RANGE **HOME**

5 YEARS WARRANTY COMPRESSOR QUALITY COMMITMENT

3 YEARS WARRANTY TOTAL QUALITY COMMITMENT

A++ SEER

A+ SCOP

A+++ SCOP Warmer



Technical data

CONSOLE

L01 R32

R-32

DC inverter — DC Inverter compressor and fans

LED — LED Display

Defrost function

Turbo — Turbo button

Night mode

Dehumidifier

Auto-reset

Auto-diagnosis

24 — Timer

Remote control

MODEL			HTW-F-026L01R32	HTW-F-035L01R32	HTW-F-052L01R32
		IN.	HTW-FI-026L01-R32	HTW-FI-035L01-R32	HTW-FI-052L01-R32
		OUT.	HTW-FO-026L01-R32	HTW-FO-035L01-R32	HTW-FO-052L01-R32
Power Supply		V,P,HZ	220-240V (1 Phase ~ 50Hz) / Outdoor unit		
PERFORMANCE					
Cooling	Capacity (min. - max.)	kW	2,7 (0,7 - 3.400)	3,5 (0,8 - 4.400)	5,2 (1,2 - 6.600)
		Btu/h	9.212 (2.388 - 11.601)	12.010 (2.730 - 15.013)	17.742 (4.299 - 22.519)
	Consumption (min. - max.)	W	720 (170 - 1.300)	1.000 (160 - 1.500)	1.600 (380 - 2.450)
	Current	A	3,5	4,48	7,1
	SEER	-	7,2	7	6,6
	Energy class	Cold	A++	A+++	A+++
Heating	Capacity (min. - max.)	kW	2,9 (0,6 - 3,5)	3,8 (1,1 - 4,4)	5,2 (1,1 - 6,8)
		Btu/h	9.895 (2.047 - 11.942)	12.966 (3.753 - 15.013)	17.742 (3.821 - 23.202)
	Consumo	W	730 (130 - 1.350)	960 (165 - 1.500)	1.480 (350 - 2.500)
	Current	A	3,6	4,3	6,7
	SCOP	-	5,3	5,3	5,1
	Energy class	Heat	A+	A+	A+
FEATURES					
Indoor unit	Sound power	dB(A)	50/45/42/34	54/48/43/35	57/52/47/41
	Sound pressure	dB(A)	39/33/29/23	44/38/33/25	47/42/37/31
	Air flow	m^3/h	500/410/330/250	600/480/400/280	700/580/460/320
	Operating temperature	°C	16~30	16~30	16~30
Outdoor unit	Sound power	dB(A)	60	62	65
	Sound pressure	dB(A)	49	52	57
	Air flow	m^3/h	1.600	2.200	3.200
	Operating temperature cold/heat	°C	(-15 ~ 43)/(-22 ~ 24)	(-15 ~ 43)/(-22 ~ 24)	(-15 ~ 43)/(-22 ~ 24)
Refrigerant	Type/Charge	R32/Kg	0,55	0,75	0,95
	Additional charge>5	g/m	16	16	20
Climatized perimeter (according to room conditions)		m^2	19	25	37
DIMENSIONS AND WEIGHT					
Indoor unit	Net dimensions (WxHxD)	mm	700×600×215	700×600×215	700×600×215
	Net weight	Kg	15,5	15,5	15,5
Outdoor unit	Net dimensions (WxHxD)	mm	782x540x320	848x596x320	965x700x396
	Net weight	Kg	27,5	30,5	46
CONNECTIONS					
Refrigerant pipe	Liquid-Gas	inch	1/4"-3/8"	1/4"-3/8"	1/4"-1/2"
	Max. length	m	15	20	25
	Max. slope	m	10	10	10
Electrical connections	Supply	mm	2x2,5+T	2x2,5+T	2x2,5+T
	Connection	mm	3x1,5+T	3x1,5+T	3x1,5+T
EAN CODE	Set		8435483816961	8435483816954	8435483816947

HTW reserves the right to change models and technical data without prior notice. Valid information except typographical or printing error.