





Easy to carry

Thanks to small dimensions and handle located at the top is easy to transport.

LED Display

Shows: Temperature, mode (cold/warm), function status (In: Turbo), cleaning reminder, filter change, etc.

Fill Level Indicator

The filling level of the reservoir is displayed.

Anti-ice function

When the unit goes into defrost mode, it absorbs energy through a hot gas tube, so it doesn't affect the water temperature.

Timer 24h

Unit can be set to turn on or off at anytime in a day.

Self-diagnosis

Once abnormal operation or parts failure happen, the unit will shut off automatically to protect the system. Meanwhile it will indicate protection or error code for fast service.

Auto-restart function

The unit is able to remember all the original settings that were set before the power failure and automatically returns to those settings when the power is restored.

Compact design

The unit is designed with smaller dimension, which is easy to install and transport, and saves the cost.

Visualization of the humidity in real time

MODELS			HTW-DH-16P04
Power supply		V,P,HZ	220-240V (1 Ph ~ 50Hz)
Type of control		-	Electronic
			PERFORMANCE
Deshumidifying capacity		L/Day	16
Input		W	280
Rated current		A	1,25
			FEATURES
Sound level (H/L)		dB(A)	45/43
Air flow (H/L)		m^3/h	100/80
Design pressure		Mpa	1,7/0,6
Water tank capacity		L	3/3,5
Refrigerant	Type	-	R134A
	Charged	Kg	0,12
			APLICATION
Ambient operating temperature		°C	5~35
Area aplication		m^2	20
			DIMENSIONS & WEIGHT
Net dimensions (WxHxD)		mm	353x496x225
Gross dimensions (WxHxD)		mm	396x530x274
Weight net/gross		Kg	12/13
EAN CODE			**8436553743200**