





Refrigerant gas


Easy to carry


Incorporates wheels



LED Display


Fill level indicator


Removable water tank


Anti-ice function


Auto-restart function



Timer 24h


Self-diagnosis


Continuous external drain plug



Low sound pressure level (dB)*according to model



Great dehumidifying production capacity

Easy to carry

Thanks to small dimensions and handle located at the top is easy to transport.

LED display

Shows: Temperature, mode (cold/warm), function status (In: Turbo), cleaning reminder, filter change, etc.

Fill Level Indicator

The filling level of the reservoir is displayed.

Anti-ice function

When the unit goes into defrost mode, it absorbs energy through a hot gas tube, so it doesn't affect the water temperature.

Self-diagnosis

Once abnormal operation or parts failure happen, the unit will shut off automatically to protect the system. Meanwhile it will indicate protection or error code for fast service.

Auto-restart function

The unit is able to remember all the original settings that were set before the power failure and automatically returns to those settings when the power is restored.

Timer 24h

Unit can be set to turn on or off at anytime in a day.

Compact design

The unit is designed with smaller dimension, which is easy to install and transport, and saves the cost.

Visualization of the humidity in real time

Removable water tank

The tank is easily removable to be emptied.

MODELS			HTW-DH-20P06
Power supply		V,P,HZ	220-240V (1 Ph ~ 50Hz)
Type of control		-	Electronic
			PERFORMANCE
Deshumidifying capacity		L/Day	20
Input		W	260
Rated current		A	1,30
			FEATURES
Sound level (H/M/L)		dB(A)	48/46/44
Air flow (H/M/L)		m^3/h	185/165/145
Design pressure		Mpa	1,7/0,6
Water tank capacity		L	3,6/4,2
Refrigerant	Type	-	R134A
	Charged	Kg	0,13
			APLICATION
Ambient operating temperature		ºC	5~35
Area aplication		m^2	28
			DIMENSIONS & WEIGHT
Net dimensions (WxHxD)		mm	351x492x260
Gross dimensions (WxHxD)		mm	407x530x329
Weight net/gross		Kg	15/17
EAN CODE			**8436553743224**