PORTABLE Dehumidifier

X6PW





- Easy to carry
- Incorporate wheels
- LED Display
- Fill level indicator
- Self-diagnosis
- Turbo button
- Anti-ice function
- Auto-restart function
- Timer 24h
- Low sound pressure level (dB)*according to model
- 30 L/Day Great dehumidifying production capacity
- 40 L/Day Great dehumidifying production capacity
- 50 L/Day Great dehumidifying production capacity

LED display

Shows: Temperature, mode (cold/warm), function status (In: Turbo), cleaning reminder, filter change, etc.

Auto-restart function

The unit is able to remember all the original settings that were set before the power failure and automatically returns to those settings when the power is restored.

Anti-ice function

When the unit goes into defrost mode, it absorbs energy through a hot gas tube, so it doesn't affect the water temperature.

Self-diagnosis

Once abnormal operation or parts failure happen, the unit will shut off automatically to protect the system. Meanwhile it will indicate protection or error code for fast service.

Timer 24h

Unit can be set to turn on or off at anytime in a day.

Compact design

The unit is designed with smaller dimension, which is easy to install and transport, and saves the cost.

Fill Level Indicator

The filling level of the reservoir is displayed.

MODELS		HTWDB30X6PW	HTWDB40X6PW	HTWDB50X6PW
Power supply	V,P,HZ	220-240V (1 Ph ~ 50Hz)	220-240V (1 Ph ~ 50Hz)	220-240V (1 Ph ~ 50Hz)
Type of control	-	Electronic	Electronic	Electronic
PERFORMANCE				
Deshumidifying capacity	L/Day	30	40	50
Input	W	465	560	775
Rated current	A	2,5	2,7	3,6
FEATURES				
Sound level (H/L)	dB(A)	54/52	52/51	52/51
Air flow (H/L)	m^3/h	210/180	345/320	345/320
Design pressure	Mpa	4,2/1,5	4,2/1,5	4,2/1,5
Water tank capacity	L	3	6	6
Refrigerant Type	-	R410A	R410A	R410A
Refrigerant Charged	Kg	0,22	0,19	0,29
APLICATION				
Ambient operating temperature	°C	5~35	5~35	5~35
Area aplication	m^2	58-73	80-95	100-115
DIMENSIONS & WEIGHT				
Net dimensions (WxHxD)	mm	386x500x260	392x616x282	392x616x282
Gross dimensions (WxHxD)	mm	420x537x297	427x657x327	427x657x327
Weight net/gross	Kg	15,3/16,4	18,1/19,5	19,8/21,2
EAN CODE		**8435483800052**	**8435483800069**	**8435483800076**