PORTABLE Air conditioner

Only cold **P14**





R410A
Refrigerant gas

Easy to carry

LCD
LCD display

MODE
Various operating models

Easy
Easy installation

Auto-restart function

Self-diagnosis

Evaporation system

Remote control

54
Low sound pressure level (dB)* according to model

A
EER
Energy class EER

Evaporation system

Automatically evaporates condensed water, avoiding the continuous use of the tank.

Self-diagnosis

Once abnormal operation or parts failure happen, the unit will shut off automatically to protect the system. Meanwhile it will indicate protection or error code for fast service.

Compact design

The unit is designed with smaller dimension, which is easy to install and transport, and saves the cost.

Operating modes

- Fan mode
- Air conditioner mode
- Deshumidifying mode

Auto-swing function

The unit has an automatic deflector oscillation horizontally. In this way, it may vary automatically the air exit angle in every detection.

LCD display

Shows: Temperature, mode (cold/warm), function status (In: Turbo), cleaning reminder, filter change, etc.

Auto-restart

The unit is able to remember all the original settings that were set before the power failure and automatically returns to those settings when the power is restored.

Timer 24h

Unit can be set to turn on or off at anytime in a day.

HTW
HIGH TECHNOLOGY WORLD
GIA GROUP

MODELS			HTW-PCS-021P14
Power supply		V,P,HZ	220-240V (1 Ph ~ 50Hz)
			PERFORMANCE
Cooling capacity	Capacity	kW	2,05
		Frig/h	1765
		Btu/h	7000
	Input	W	760
	Rated current	A	3,9
	EER	-	2,6
	Energy class	Cooling	A
			FEATURES
Sound level		dB(A)	54
Air flow (H/M/L)		m^3/h	300
Heatable perimeter (according to the conditions of the room)		m^2	16
Operation temperature		°C	5~35
Selectable temperature		°C	16~31
Deshumidifying		L/h	0,8
Refrigerante	Type	-	R410A
	Charged	Kg	0,3
			DIMENSIONS & WEIGHT
Net dimensions (WxHxD)		mm	328x678x305
Gross dimensions (WxHxD)		mm	378x345x870
Weight net/gross		Kg	21/23
EAN CODE			**8435483800847**