

3 Operating **MODES**

- **DESHUMIDIFYING** mode
- **FAN** mode
- **AIR CONDITIONER** mode

AUTOMATIC EVAPORATION SYSTEM





Refrigerant gas



Window kit included



Various operating modes



Easy installation



Multifunction touch display



Incorporates wheels



Auto-restart function



Auto-swing function



Self-diagnosis



Evaporation system



Deshumidifying



Continuous external drain plug



Easy to carry



Remote control



Low sound pressure level (dB)*according to model



Energy class EER

Auto-restart function

The unit is able to remember all the original settings that were set before the power failure and automatically returns to those settings when the power is restored.

Timer 24h

Unit can be set to turn on or off at anytime in a day.

Evaporation system

Automatically evaporates condensed water, avoiding the continuous use of the tank.

Self-diagnosis

Once abnormal operation or parts failure happen, the unit will shut off automatically to protect the system. Meanwhile it will indicate protection or error code for fast service.

Compact design

The unit is designed with smaller dimension, which is easy to install and transport, and saves the cost.

Operating modes

- Fan mode
- Air conditioner mode
- Deshumidifying mode

MODELS			HTW-PC-026P15	HTW-PC-035P15
Power supply		V,P,HZ	220-240V (1 Ph ~ 50Hz)	
			PERFORMANCE	
Cooling capacity	Capacity	kW	2,8	3,35
		Frig/h	2408	2881
		Btu/h	9000	11000
	Input	W	1070	1280
	Rated current	A	4,8	5,5
	EER	-	2,62	2,62
	Energy class	Cooling	A	A
			FEATURES	
Sound level (H/M/L)		dB(A)	53/52/51	55/54/53
Air flow		m^3/h	300	330
Heatable perimeter (according to the conditions of the room)		m^2	11~18	13~21
Operation temperature		°C	17~35|-	17~35|-
Deshumidifying		L/h	1,2	1,6
Capacidad depósito auxiliar de agua		L	0,4	0,4
Refrigerant	Type	-	R410A	R410A
	Charged	Kg	0,580	0,500
			DIMENSIONS & WEIGHT	
Net dimensions (WxHxD)		mm	435x715x350	435x715x350
Gross dimensions (WxHxD)		mm	485x865x395	485x865x395
Weight net/gross		Kg	30/34	32/36
EAN CODE			**8435483801134**	**8435483801066**