PORTABLE Air conditioner

Heat pump **P16**





R410A
Refrigerant gas

Easy to carry

Heat pump *according to model

MODE
Various operating modes

Easy
Easy installation

Auto-restart function

Auto-swing function

Self-diagnosis

Evaporation system

Remote control

54
Low sound pressure level (dB)*according to model

A
EER
Energy class EER

Heat pump (according to model)

This portable air conditioner incorporates a standard heat pump (without electric resistance).

Auto-restart function

The unit is able to remember all the original settings that were set before the power failure and automatically returns to those settings when the power is restored.

Timer 24h

Unit can be set to turn on or off at anytime in a day.

Evaporation system

Automatically evaporates condensed water, avoiding the continuous use of the tank.

Self-diagnosis

Once abnormal operation or parts failure happen, the unit will shut off automatically to protect the system. Meanwhile it will indicate protection or error code for fast service.

Compact design

The unit is designed with smaller dimension, which is easy to install and transport, and saves the cost.

Operating modes

- Fan mode
- Air conditioner mode
- Deshumidifying mode
- Heat pump mode

HTW
HIGH TECHNOLOGY WORLD
GIA GROUP

MODELS			HTW-PC-026P16	HTW-PCS-026P16	HTW-PB-026P16	HTW-PBS-026P16
Power supply		V,Ph,HZ	220-240V (1 Ph ~ 50Hz)			
PERFORMANCE						
Cooling capacity	Capacity	kW	2,61	2,61	2,61	2,61
		Frig/h				
		Btu/h	9000	9000	9000	9000
	Input	W	990	990	990	990
	Rated current	A	4,4	4,4	4,4	4,4
	EER	-	2,6	2,6	2,6	2,6
	Energy class	Cooling	A	A	A	A
Heating capacity	Capacity	kW	-	-	2,61	2,61
		Frig/h	-	-	-	-
		Btu/h	-	-	9000	9000
	Input	W	-	-	870	870
	Rated current	A	-	-	3,9	3,9
	COP	-	-	-	2,8	2,8
	Energy class	Heating	-	-	A	A
FEATURES						
Sound level		dB(A)	54	54	54	54
Air flow		m^3/h	380	380	380	380
Heatable perimeter (according to the conditions of the room)		m^2	11~18	11~18	11~18	11~18
Operation temperature		°C	17~35|-	17~35|-	17~35|5~30	17~35|5~30
Deshumidifying		L/h	1,17	1,17	1,17	1,17
Capacity auxiliary water tank		L	0,4	0,4	0,4	0,4
Refrigerant	Type	-	R410A	R410A	R410A	R410A
	Charged	Kg	0,50	0,50	0,50	0,50
DIMENSIONS & WEIGHT						
Net dimensions (WxHxD)		mm	320x730x370	320x730x370	320x730x370	320x730x370
Gross dimensions (WxHxD)		mm	372x864x402	372x864x402	372x864x402	372x864x402
Weight net/gross		Kg	24/27	24/27	24/27	24/27
EAN CODE			**8435483801035**	**8435483801059**	**8435483801042**	**8435483801165**